

Date tehnice pentru produs: HSELS249LP

# Splicebox, 24 fibre, LC, 9/ 125µm OS2, culisant, 19", 1 UV , ECO



## SCHRACK-Info

### Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:  
for 12 LC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:  
Chassis: 1,0mm  
Sliding tray: 1,25mm  
Frontpanel: 1,4mm  
19" holder: 1,5mm

### SPLICE-CASSETTES

- For shrink splice protectors  
up to 12 fibres: 1 splice-cassette

up to 24 fibers: 2 splice-cassettes

## STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

## Fișe tehnice

Lățime netă (mm)	480,00
Înălțime (mm)	44,00
Adâncime netă (mm)	242,00
Masă netă (kg.)	2,53
Temperatura minimă a mediului ambiant (°C)	-10
Temperatura maximă a mediului ambiant (°C)	70
Pierdere de inserție tipică (dB)	< 0,2
Pierderi pe retur tipice (dB)	> 50
Fibră	9/125 OS2 Singlemode / G.652.D
Număr fibre	24

## Tabel articole

Descriere	Cod comandă
Splicebox, 24 fibre, LC, 9/125µm OS2, culisant, 19", 1UV, ECO	HSELS249LP
<b>Accesorii opționale</b>	
Tub termocontractibil 60mm pentru fibră optică LVZ0007	HELSP00011
Tub termocontractibil 40mm pentru fibră optică LVZ0006	HELSP00010
Patchcablu duplex, LC/LC, 9/125µm OS2, 2m	HLP29LL02F
Patchcablu duplex, LC/LC, 9/125µm OS2, 5m	HLP29LL05F
Patchcablu duplex, LC/SC, 9/125µm OS2, 2m	HLP29LC02F
Patchcablu duplex, LC/SC, 9/125µm OS2, 5m	HLP29LC05F
Patchcablu duplex, LC/FC, 9/125µm OS2, 2m	HLP29LF02F