	Low Power CameraBG66DR			
	Pro	duct Image	Product features	
			★Stable 4G connection	
	h		★ Remote active wake-up, two-way voice intercom	
			★ Quick start, start recording within 400ms	
			★Intelligent detection of human movement, intelligent alarm push	
			★8000mAh battery powered, low battery reminder	
	4		*Low power system optimization	
	803		★Free cloud storage to save alarm videos	
		()	*Dual lens dual recording to guard different directions	
	0		* Dual lens linkage, automatic zoom	
			* Dual light source, full color day and night	
			*Low power and corded power compatible design	
No.	Sorts	Туре	Parameters	
1		Operating system	Linux	
2	System	Online visitor	Supports 4 visitors at the same time	
	Collection	СРИ	T40N	
		Image sensor	GC2083+GC2083	
		Minimum illumination	0.8Lux/F1.4 (color mode), 0.3Lux/F1.4(B&W mode)	
		Lens	Bullet camera: focal length 4mm, 1G3P Dome	
		Lens	camera: focal length 4mm, 1G3P	
		Sensor performance	Support automatic white balance, automatic gain control and automatic	
		·	backlight compensation	
		PTZ	Horizontal 305°, vertical 90°	
		Viewing angle	Bullet camera: 100° diagonal, dome camera: 60° diagonal	
	Video	Night vision	Full color night vision, dual light source, 6 infrared lights+6 white lights	
		Compression standard	H.264 /MJPEF/JPEG	
		Multi stream	Main stream: 1080P/15fps, sub stream:360P/15fps	
3			When the IR night vision function is enabled, IR and ICR are automatically	
		IR control	detected; when the IR night vision function is disabled, IR is off and ICR is fixed	
		Bit rate	in the day vision mode. CBR/VBR two rate control modes, and the output rate range is 128~4096kbps	
		Image adjustment	Vertical, horizontal adjustable, OSD display	
			• • • • • • • • • • • • • • • • • • • •	
	Audio	Input	Built-in-38dB microphone	
4		Output	Built-in 8Ω1W speaker	
		Sampling frequency/bit width	8KHz/16bit	
		Compression standard/Bit Rate	G711A	
		Humanoid detection	Humanoid detection, filtering invalid video content	
5		Area detection	Free daub, only monitoring the areas concerned by users	
	AI	Smart notification sound	Different devices push different sounds, so that you can know exactly which	
		Intelligent alarm sound	device is triggered Set different equipment alarm sounds according to different scenarios	
		More AI functions (testing)	Pets, vehicles, parcels, etc	
			Use APP to scan the QR code on device to add; Use the device to scan QR code	
6	Network	Networking	on APP to add	
		Cat1 China	FDD:B1/B3/B5/B8	
			TDD:B34/B38/B39/B40/B41	
		Cat4 Overseas	European/Japanese/US versions	
7 8	Key/interface Storage	Key 1	On/Off key	
		Reset key	long press to restore factory settings	
		External TF card	Support TF card (up to 256GB)	
		Cloud storage	One-day free loop cloud storage	
9	Alarm	Sound light alarm	Sound light alarm , 6 infrared lights+6 white lights, full color night vision	
		Alarm detection	Support for human detection, PIR infrared human detection for 10 meters	
10	Physical Indicators	Rated voltage	DC5V±5%	
		Power supply	Equipped with 8000mAh battery	
		Consumption	Sleep standby 300uA , working : 400MA-1.5A max	
			Temperature: -10 ~ 55°C; Humidity: <90%	
		Weight	Net weight: 770g; Gross weight: 1680g	
		Size	Camera : 210*115*206mm	
		Packing list	Camera * 1, manual * 1, solar panel * 1, solar panel bracket * 1	