

U3

300Mbps Mini Wireless N USB Adapter

Tenda's 300Mbps Mini Wireless N USB Adapter U3 is designed to connect your laptop or desktop to a wireless network and enjoy high speed wireless performance. The fingertip design makes the adapter convenient and easy to carry around. What's more, the U3 supports the soft AP mode. In this mode, U3 functions an AP to turn the wired network into a wireless one, making the networking of wireless LAN quick and easy. It is compatible with many operating systems, allowing connection of computers, notebooks and other wireless devices.



1. Miniature Design

Mini-sized design for convenient portability , there's no need to worry about blocking adjacent USB interfaces




2. 300Mbps Wireless N Speed

With wireless speeds of up to 300Mbps and advanced MIMO technology, the U3 provides you with a fast, reliable wireless connection for lag-free online gaming and video streaming



3. SoftAP Mode

Turn a wired internet connection to a PC or Laptop into a Wi-Fi hotspot



4. Compatibility

Compatible with Windows XP/7/8/8.1/10, MAC OSs 10.6 - 10.12, Linux Os,and ideal for Raspberry Pi / Pi2 (Raspbian/Ubuntu MATE/OSMC/LIBREELEC/WINDOWS 10 IOT)

* Plug & Play on Windows 10

Specifications

HARDWARE FEATURES	
Interface	USB2.0
Dimensions (W X D X H)	37.5mm*19.5mm*8.9mm(L x W x H)
Antenna Type	Internal PIFA Antenna
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Frequency	2.400~2.4835GHz
Signal Rate	11b: Up to 11Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11n: Up to 300Mbps(dynamic)
Transmit Power	<20dBm (EIRP)
Wireless Modes	Station Mode, SoftAP Mode
Wireless Security	64/128-bit WEP,WPA-PSK / WPA2-PSK,WPA / WPA2
OTHERS	
Certification	CE, FCC,RoHS
Package Contents	1*Wireless Adapter U3,1*Resource CD,1* Install Guide
System Requirements	windows10,Windows 8.1, Windows 8,Windows 7,Windows XP, Mac OS 10.7~10.12, Linux
Environment	Operating Temperature: 0°C~40°C (32°F~104°F)
	Storage Temperature: -40°C~70°C (-40°F~158°F)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing
Related Products	F3、FH456、A9

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

6-8 Floor, Tower E3, No.1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

Phone: (86 755)2765 7180 Fax: (86 755)2765 7178

Email: sales@tenda.com.cn support@tenda.com.cn

Website: <http://www.tenda.com.cn>

©2016 SHENZHEN TENDA TECHNOLOGY CO.,Ltd, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co.,Ltd in China and/or other countries. Other Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.