

PRODUCT DATASHEET

DoorLED UpDown Sensor 4000K White

Door LED UpDown | Mobile luminaire for entrance areas, light outlet up and down



Areas of application

- For a very large range of uses
- Indoor and outdoor
- Entrance lighting
- Corridors
- Patios, balconies

Product benefits

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and quick installation
- Accessories for flexible mounting options included

Product features

- Integrated light and motion sensor
- Available in two housing colors
- Type of protection: IP54



TECHNICAL DATA

Electrical data


Nominal wattage	0.80 W
Nominal voltage	6 V
Mains frequency	0 Hz
Nominal current	132.000 mA
Max. no. of lum. on circuit break. B16 A	-
Max. no. of lum. on circuit break. C10 A	-
Max. no. of lum. on circuit break. C16 A	-
Protection class	III
Operating mode	Battery

Photometrical data

Luminous flux	40 lm
Luminous efficacy	50 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdc _m

Dimensions & Weight

Length	41.00 mm
Width	70.00 mm
Height	90.00 mm
Product weight	176.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Acrylonitrile butadiene styrene (ABS)
Cover material	Plastic
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	0...+25 °C
Temperature range at storage	-20...+50 °C
Type of protection	IP54
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
---------------------------	---------

Sensor

Type of sensor	Light / Motion
Sensor technology	Passive infrared (PIR)

Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

EQUIPMENT / ACCESSORIES

– Batteries included: 4x 1.5 V LR6 (AA)

DOWNLOAD DATA

DOWNLOAD DATA



Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075472778	Blister 1	42 mm x 140 mm x 195 mm	196.00 g	1.15 dm ³
4058075472785	Shipping box 6	300 mm x 154 mm x 210 mm	1293.00 g	9.70 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.