

# MARINE WCP1A

## Conventional Marine Approved Weatherproof Manual Call Point

Your Safety, Our Technology

### Features

- ▶ Complies with EN54-11
- ▶ Push-fit terminals can accommodate up to a 2.5mm<sup>2</sup> solid conductor.
- ▶ Other colours available on request
- ▶ IP rated to IP67
- ▶ Approved by GL



### Description

The WCP1A is a Conventional Marine Approved Weatherproof call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals. The unit features a 'Non Frangible Plastic' element and a weatherproof Housing to IP67, which means it can be mounted in the most severe environmental conditions without water ingress.

### Specification

Ordering Codes	SLR-E-IS
	SLR-E-IS(WHT)
Nominal operating resistance	15 – 30 VDC
Maximum contact resistance	50 $\mu$ A
Ingress Protection Rating	40 mA
Operating Temperature Range	-10 °C to + 50 °C
Storage Temperature Range	-30 °C to + 70 °C
Maximum Humidity	95% RH - Non Condensing (at 40 °C)
Colour / Case Material	Ivory or White / ABS
Weight (g) / Diameter (mm) / Height (mm)	115 / 100 / 38
Approvals	DNV GL

### Ordering Codes

#### Product

Conventional Marine Approved Weatherproof Manual Call Point  
Non-Frangible Element

#### Part Number

SLR-E-IS/SIL  
KAC/EWS/HE

### Approvals

