ND 200 LSN Panic Button

www.boschsecurity.com





- ► Panic button in LSN technology
- ▶ For connecting to a LSN intrusion panel via LSN bus
- ► Tamper contact
- ▶ Surface- or flush-mounting of the cable
- ▶ Compatible with optional cap with cover

The panic button is used for unobtrusively and manually triggering alarms at work places that are in potential danger of being held up, such as banks, jewelry shops, businesses, private households etc. The panic button is connected via LSN.

Certifications and approvals

Region	Certification	
Germany	VdS	G 101037, C ND 200 LSN G 101037
Europe	CE	ND 200 LSN

Parts included

Quantity	Component	
1	Panic button	
1	Adhesive seal	
1	Installation note	

Technical specifications

Electrical

Minimum operating voltage in VDC	12
Maximum operating voltage in VDC	30
Maximum current consumption in mA	0.5

Mechanical

Dimension in cm (Ø x D)	8.1 x 3.1
Weight in g	70
Housing material	ABS
Color (housing)	RAL 9002
Color (cover)	Grey

Environmental

Minimum operating temperature in °C	0
Maximum operating temperature in ${}^{\circ}\!\text{C}$	50

2 | ND 200 LSN Panic Button

Maximum relative humidity in %	95
Environmental class	II
Protection class	IP40

Ordering information

ND 200 LSN Panic Button

LSN panic button for unobtrusively and manually triggering alarms Order number 4998117564

Accessories

Cap with cover

For additional protective cover to prevent false alarms Order number 3902115343

Represented by:

Europe, Middle East, Africa: Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com **Germany:**Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn Germany www.boschsecurity.com

North America: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia