

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	Image Sensor	1/3 inch 1440p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens	4mm-6mm
	Night vision	Dual filter automatic switching, dual light source, illumination distance 15-30 meters.
	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data rate	Main stream: 1440p(2560×1440)@25fps, Substream: 360p(640×360)@15fps
	Bit rate /maximum frame rate	128~4096kbps/25fps
	Image adjustment	Adjustable brightness and contrast
Audio	Input	Built-in -38dB microphone
	Output	Built-in 8 Ω 1W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/bit Rate	G.711/64kbps
Network	Network interface	10Mbps/100Mbps adaptive/RJ45 interface
	Network protocol	TCP/IP, HTTP, TCP, UDP, DHCP, DNS, NTP, RTSP, P2P etc.
	Wireless network	
	Wireless frequency	2.4G
	Wireless security encryption	
Pan&Tilt	Rotation angle	Horizontal 350°/Vertical 90°
	Preset position	Supports 16 presets (mobile app only supports 5)
Storage	Storage	Supports T-Flash card(max supports 256GB); Cloud Storage;NVR;NAS;
Alarm	Alarm detection	Supports motion detection, humanoid detection, human tracking, Voice and flash alarm, illumination function,timing white light ON/OFF
Physical indicators	Rated voltage	DC12V
	Power consumption	Rated power: 4.5W (infrared light on)/maximum power: 11W (pan&tilt on)
	Operating condition	Temperature: -10~50℃; Humidity: <90%
	Weight	(Note: in kind prevail)
	Package size	(Note: in kind prevail)