

**CABLU COAXIAL RG59 CUPRU THB/ROLA 305M/ALB****Rola la 305 m**

- Cablu coaxial RG 59 CUPRU
- Rolă: 305m
- Alb
- Marca THB

**TECHNICAL SPECIFICATIONS:****Specification : VIDEO (RG-59 B/U Coax)**

<b>Conductor</b>	<b>Copper wire with overall diameter 0.60+/-0.01mm</b>
<b>Insulation</b>	<b>Solid polyethylene (SPE) with overall diameter 3.70+/-0.1mm</b>
<b>Shield</b>	<b>Copper clad Aluminum wire</b>
	<b>Nominal diameter - 0.12mm</b>
	<b>No of wires end - 6 cores/ spindle</b>

**No of spindles - 16 groups**

**Covering 80-90.0%**

**Pitch 20.8mm**

**Outer Jacket 6.0+/-0.10mm White PVC**

**Specification : POWER (2 core/ 0.75)**

**Inner conductor Copper-clad aluminum wire with overall diameter 24/0.2+/-0.005mm x2**

**Insulation 2.10+/-0.1mm x2 Red & Black PVC**

#### **ELECTRICAL PROPERTIES**

**Characteristic Impedance Max. 9.4  $\Omega$ /100m**

**Inner conductor resistance Max. 2.5 %**

**Capacitance Min. 5000M $\Omega$ /KM**

**Attention (dB/10m,100m,20°C) 1.3dB/10m max@100MHz**

**1.9dB/10m max@200MHz**

**4.6dB/10m max@1000MHz**

**29.50dB/100m max@400MHz**