

 <p style="font-size: 24px; font-weight: bold; margin-left: 200px;">CB69</p>		
	<b>Chip</b>	<b>Ingenic T31 ZL</b>
	<b>Sensor</b>	<b>GC2063</b>
	<b>Pixel</b>	<b>3MP</b>
	<b>Features</b>	<ol style="list-style-type: none"> <li><b>1. Exclusive private model, 3MP, 2.5 inch ;</b></li> <li><b>2. PIR + Radar dual induction alarm recording, Within 1 second recording;</b></li> <li><b>3. Support 20000 mAh battery power supply and Low-battery alert;</b></li> <li><b>4. IP66 waterproof, rainproof &amp; dustproof, Two-way talk;</b></li> <li><b>5. Cloud Storage, TF card storage, Max supports 256G;</b></li> <li><b>6. Humanoid detection and alarm pushing;</b></li> <li><b>7. Free Cloud Storage recording;</b></li> </ol>
<b>Sorts</b>	<b>Type</b>	<b>Parameters</b>
<b>System</b>	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	1/2.9 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens/Viewing angle	3.6mm@F2.0/101° Diagonal
	Night vision	IR-CUT with auto-switching, 6 pcs IR LED lights; Irradiation distance: 10~15 m
	Compression standard	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Data Rate	Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps
	Image adjustment	Brightness and contrast are adjustable

**Shenzhen VStarcam Technology Co., Ltd**

<b>Audio</b>	Input	Built-in —38dB microphone
	Output	Built-in 8Ω2 W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/64kbps
<b>Network</b>	Network configuration	QR code, AP network configuration
	Network protocol	TCP/IP, HTTP, TCP, UDP, DHCP, DNS, NTP, P2P etc.
	Wireless network	IEEE802.11b/g/n; Supports AP mode
	Wireless frequency	2.4~2.4835GHz
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
<b>Pan &amp; Tilt</b>	Pan & Tilt	Pan 345° /Tilt 35°
	Preset position	Supports 16 (Mobile phone App supports 5) preset positions
<b>Storage</b>	Storage functions	Supports T-Flash card(max supports 256GB); Cloud storage
<b>Alarm</b>	Alarm detection	Radar detection; Humanoid detection
<b>Physical Indicators</b>	Rated voltage	DC5V±5%
	Power supply	Supports four 18650 or four 21700 batteries
	Power	Rated power: 5W (with IR LED lights ON)/Max power: 11W (with Pan & Tilt ON)
	Operating condition	Temperature: -10~50°C; Humidity: <90%
	Weight	Net: TBD (Note: in kind prevail)
	Package size	TBD