


	CS663DR	
<b>Sorts</b>	<b>Type</b>	<b>Parameters</b>
<b>Collection</b>	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/Image sensor	Ingenic T40, 2MP, dual lens, 1/3 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens	2.8mm-6mm
	Night Vision	IR-CUT with auto-switching, dual light source, irradiation distance 15-30 meters
	Compression standard	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Data rate	Main stream:1080p(1920*1080)@25fps; Substream:360p(640*360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/25fps
	Image adjustment	Adjustable brightness and contrast
<b>Audio</b>	Input	Built-in - 38dB microphone
	Output	Built-in 8 Ω 2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/64kbps
<b>Network</b>	Network interface	10Mbps/100Mbps adaptive /RJ45 interface
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	Wireless network	IEEE802.11b/g/n
	Wireless frequency	2.4G
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
<b>Pan&amp;Tilt</b>	Rotation angle	Horizontal 350 °/Vertical 90 °, can be installed with 360 ° rotation
	Preset position	Supports 16 presets (mobile app only supports 5)
<b>Storage</b>	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage;NVR; NAS
Alarm	Alarm detection	Support motion detection, humanoid detection, human tracking, alarm voice prompts, flash and illumination functions, and timed activation and shutdown of white light.
Physical indicators	Rated voltage	DC12V
	Power consumption	Rated power: 4.5W (infrared light on)/maximum power: 11W (PTZ on)



我的安全，我做主

**Model: CS663DR**

	Operating condition	Temperature: -10~50°C; Humidity: <90%
	Weight	Note: in kind prevail
	Package size	Note: in kind prevail