

RLK8-520D4-NVR-Kit-IP-Camera-Specifications			
	Model	RLC-520	
Note:	The cameras of the kit cannot work without the NVR.		
Video & Audio	Image Sensor	1/2.7" CMOS Sensor	
	Video Resolution	2560x1920 (5.0 Megapixels) at 30 frames/sec	
	Lens	f=4.0mm fixed; F=2.0, with IR-cut filter	
	Video Format	H.264	
	Field of View	Horizontal: 80°	
		Vertical: 58°	
	Day & Night	Auto-switching with IR-cut filter	
	Night Vision	30 meters (100ft) (LED: 18pcs/14mil/850nm)	
Audio	Audio recording		
Power	PoE	IEEE 802.3af, 48V Active	
	DC Power	DC 12.0V 1A, <8W	
Interface	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps; RJ45	
	Audio	Built-in microphone	
Software Features	Frame Rate	Mainstream: 2fps - 30fps (default: 30fps)	
		Substream: 4fps - 15fps (default: 7fps)	
	Code Rate	Mainstream: 1024Kbps - 8192Kbps (default: 6144Kbps)	
		Substream: 64Kbps - 512Kbps (default: 160Kbps)	
	Smart Alarm	Motion detection	
Record Mode	Motion-triggered recording; scheduled recording		
Working Environment	Temperature	Operating temperature: -10°C - +55°C (14°F - 131°F)	
	Humidity	Operating humidity: 10% - 90%	
	Waterproof	IP66	
Size & Weight	Dimension	Φ105*93mm	
	Weight	385g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/	