

TrackMix-PoE-IP-Camera-Specifications

	Model	Reolink TrackMix PoE
Video & Audio	Image Sensor	1/3"+1/2.8"CMOS Sensor
	Video Resolution	Up to: 3840 x 2160 (8.0 megapixels) at 25 frames/sec
	Lens	f=2.8mm@F=1.6, f=8mm@F=1.6
	Video Format	H.264, H.265
	Field of View	Horizontal: 104 °38 ° Vertical: 60 °21 °
	Zoom Mode	6X hybrid zoom
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 15 meters (50ft) (LED: 2pcs/850nm)
	Color Night Vision	Spotlights: 2pcs/6500K/450 lumens
	Audio	Two-way audio
Power	PoE	IEEE 802.3af, 48V active
	DC Power	DC 12.0V~2A, <12W
Interface	Power	DC power port
	System	Reset button
	Ethernet	One 10M/100Mbps RJ45
	Storage	Micro SD card slot (Max. 256GB)
	Audio	Built-in microphone and speaker
Pan&Tilt	Pan &Tilt Range	Pan: 355 °, Tilt: 0 °~90 °
	Pan Speed	2.5 °90 %s (Speed can be set)
	Tilt Speed	1.5 °60 %s (Speed can be set)
	Preset	32
	Auto Tracking	Support
Software Features	Frame Rate	Mainstream: 2fps - 25fps Substream: 4fps - 20fps
	Code Rate	Mainstream: 4096Kbps -8192Kbps Substream: 128Kbps -1228Kbps
	Browsers Supported	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarms	Motion detection; person detection; vehicle detection; pet detection (beta)
	Recording Modes	Motion/scheduled recording (default: motion recording)
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Maximal User Access	Supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams) 20 users (1 admin account & 19 user accounts);
	Work with	Google Assistant
Working Environment	Temperature	Operating temperature: -10 °C~+55 °C (14 °F~131 °F)
	Humidity	Operating humidity: 10% ~ 90%
	Waterproof	Support
Size & Weight	Dimension	228*147*110mm
	Weight	1.21KG
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .