

## Low Power Battery Bullet Camera -- CB11

Product picture		Product characteristics	
		★ Wireless connection	
		★ Remote active waking up, Two-way talk	
		★ Start quickly & start recording within 600ms	
		★ Smart PIR human detection, Smart alarm pushing	
		★ 15000mAh battery powered, Low power reminding; 21700 battery×3	
		★ Low power system optimization	
		★ Free 3 days Cloud Storage alarm video	
		★Support external 5V solar panels, continuous transmission power supply, Never power off	
		★Dual light sources, Full color day & night	
Serial number	Category	Type	Parameters
1	System	Operating system	Linux
		Online visitors	Support 4 visitors online at the same time
		App	Veese - overseas
2	Collection	Processor	T31ZL 1.5GHZ
		Memory	512Mb
		Image sensor	GC2063, 2MP,1/2.9 CMOS (pixel optional, PCB compatible)
		Minimum illumination	0.8Lux/F1.4 (Color mode), 0.3Lux/F1.4 (B&W mode)
		Lens	Standard lens 4mm, 1G3P, IR-CUT integrated
		Sensor performance	Support Automatic white balance, Automatic gain control, Automatic backlight compensation
		Viewing angle	D110 ° diagonal
3	Video	Night vision	Dual light sources, Full color day & night; 2 pcs IR LED lights+2 pcs LED lights
		Compression standard	H.265 /H.264 /MJPEF/JPEG
		Multi code stream	1080p / 15fps, 360p, JPEG capture
		IR control	IR turned on-- the Night vision ON; IR, ICR automatic detection; IR turned off-- the Night vision function disabled/ IR always OFF, ICR is fixed in the Day vision mode
		Bit rate	CBR / VBR two rate control modes, and the output rate range is 128 ~ 4096kbps
		Image adjustment	Brightness, contrast, vertical, horizontal adjustable, OSD display
4	Audio	Input	Built-in - 38dB microphone
		Output	Built-in 8 Ω 2W speaker
		Sampling frequency / Bit width	8KHz/16bit
		Compression standard / Bit rate	G711A
5	Network	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P , IPV4 etc
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4~2.4835GHz
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		Wireless connection	AP hotspot network configuration, QR code network configuration
6	Key	Key 1	Power ON/OFF
		Reset Key	Long Press to restore the factory settings
7	Storage	Storage function	Support T-Flash card (up to 256GB)
8	Alarm	Alarm detection	Support PIR human detection; Detection distance: 8m
9	Physical indicators	Rated voltage	DC5V±5%
		Power supply	Comes with 15000mAh battery power supply,3*21700 battery, supports external 5V solar panels
		Power consumption	Sleep current 500uA, Working current: 390mA
		Work environment	Working temperature: - 10 ~ 55 °C, Working humidity < 90%
		Weight	Gross weight: TBD (Note: in kind prevail)
		Size	TBD
		Packing list	Camera * 1, Bracket * 1, MICRO USB* 1, Manual * 1,(Solar panel*1, Solar panel bracket*1 optional)