



## Specifications Model: CB73

<b>System</b>	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
<b>Image Capture</b>	Image sensor	Progressive Scan CMOS
	Minimum Illumination	0.1-0.5Lux(color mode), 0 Lux(B&W mode)
	View Angle	78.4°(Diagonal)
	Night vision	6pcs 940nm 14mil patch IR LED, IR irradiation distance: 3m
<b>Video</b>	Encode format	H.264+/H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Streams	Main stream: 1920*1080@30fps Sub stream: 640*360@25fps/30fps
	Bit Rate/Max Fps	128~4096kbps/30pfs
	Image adjustment	Brightness and contrast can be adjusted
	Encode format	H.264+/H.264 main profile/Motion-JPEG/JPEG
<b>Audio</b>	Input	Built-in—38±5dB microphone
	Output	8Ω0.5W speaker
	Sampling frequency /Bit width	8KHz/16bit
	Compression standard /code rate	ADPCM/32kbps
<b>Network</b>	Ethernet	N/A
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,P2P etc
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode
	Wireless LAN Frequency	2.4~2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
<b>Memory</b>	Socket	TF Push-push socket,Maximum support 256GB
<b>Alarm</b>	Alarm Trigger	PIR detection
<b>Physical Environmental</b>	Rated voltage	DC5V±5%@Micro USB
	Power consumption	Rated power: 1.3W (with infrared lights on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: TBD g Gross: TBD g(Note: in kind prevail)
	Package size	130x90x50mm (L×W×H)