

CX410-IP-Camera-Specifications		
	Model	CX410
Video & Audio	Image Sensor	1/1.8" CMOS Sensor
	Video Resolution	Default: 2560*1440 (4.0 Megapixels)@30fps
	Lens	f=4mm F=1.0
	Video Format	H.264
	Field of View	Horizontal: 89° Vertical: 46°
	Color Night Vision	4pcs/3W/3000K/400Lumens
	Audio	Two-Way Audio
Power	PoE	IEEE 802.3af, 48V Active
	DC Power	DC 12.0V±1A, <12W
Interface	Power	DC Power Port
	System	Reset Button
	Ethernet	One 10M/100Mbps RJ45
	Storage	MicroSD Card Slot (Max. 256GB)
	Audio	Built-in Microphone & Speaker
Software Features	Frame Rate	Main Stream: 2fps - 30fps(default: 25fps) Sub Stream: 4fps - 15fps(default: 10fps)
	Code Rate	Main Stream: 2048Kbps - 6144Kbps(default: 4096Kbps) Sub Stream: 64Kbps - 512Kbps(default: 256Kbps)
	Browser Supported	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion Detection/Human Detection/Vehicle Detection/Pet Detection
	Record Mode	Motion Record/Schedule Record (Default: Motion Record)
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Working Environment	Work with	Google Assistant
	Temperature	Operating Temperature: -10°C~+50°C (14°F~122°F)
	Humidity	Operating Humidity: 10% ~ 90%
Size & Weight	Waterproof	IP 66
	Dimension	Φ67 x 187mm
Warranty	Weight	480g
	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>