

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
Collection	CPU/Image sensor	1/3 inch 1080p progressive scan CMOS sensor
	Minimum illumination	0.5 Lux (Color mode) , 0.1 Lux (B&W mode)
	Lens	4.0mm@F2.1
	Viewing angle	90.9° Diagonal
	Night vision	IR-CUT with auto-switching, 4PCS 850 patch IR LED lights; Irradiation distance: 5~10 m
Video	Compression standard	H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Data rate	Main stream: 1296p(2304×1296)@25fps Substream: 360p(640×360)@25fps
	Bit rate/maximum frame rate	128~4096kbps/25fps
	Image adjustment	Brightness, contrast, saturation, chroma are adjustable
Audio	Input/Output	Built-in -38dB microphone/Built-in 8Ω1W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G.711/32kbps
Network	Network interface	10Mbps/100Mbps adaptive /RJ45 interface
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	Wireless network	IEEE802.11b/g/n
	Wireless frequency	2.4GHz
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Storage	Storage functions	Supports T-Flash card(max supports 256GB); Cloud Storage



My safety, My rule!

Model: CS58

Alarm	Alarm detection	Supports Motion detection; Humanoid detection; Humanoid framing; Delimitation detection
Physical indicators	Rated voltage	DC12V±5%
	Power consumption	Rated power: 6W (IR on), maximum power: 6.8W
	Operating condition	Temperature: -10~50°C; Humidity: <90%
	Weight	Net weight: 345 g (Note: in kind prevail)
	Package size	228x149x93mm (LxWxH)

Shenzhen VStarcam Technology Co., Ltd

www.vstarcam.com