## R 🔺 D

## **Control Panel Comparison Chart**



Feature	EVO192	EVOHD	
Maximum Zones	192	192	
On-Board Zones	8 (16 with ATZ)	8 (16 with ATZ +	
		Tamper Input)	
Partitions	8	8	
Users	999	999	
Access Control	32 doors	32 doors	
Events Buffered	3584	3584	
PGMs	32 (5 on board)	32 (5 on board)	
Supported Cameras	16 ( HD88 )	16 ( HD88 )	
Siren	Wired / Wireless with RTX3	Wired / Wireless with RTX3	
Total Expansion Modules	254	254	
Landline Speed for Programming	300 Bps	300 / 1200 Bps	
Supports PCS Series	✓	4	
Supports IP150+ (Internet Module)	✓	✓	
Supports VDMP3 (Plug-in Voice Dialer)	<b>✓</b>	1	
In-Field Firmware Upgradeable	✓	<b>*</b>	



Security Features	MG5050+	MG5075	
StayD	4	4	
2 Serial Ports	4	-	
Built-In Transceiver	4	✓	
Maximum Zones*	32	32	
On-Board Hardwired Zones	5	5 (10 with ATZ)	
Keypad Zones	15	15	
Partitions	2	2	
Users	32	32	
Remote Controls	32	32	
PGMs	16* (4 on-board)	16* (4 on-board)	
Supported Cameras	-	15 ( HD88 )	
Events Buffered	512	512	
Wireless Sirens (SR130/SR150)	✓	✓	
Wireless Keypads	8 (K37)	8 (K37)	
Wireless Repeaters	2	2	
Expansion Bus	✓	4	
GPRS (PCS Series)	4	✓	
Internet Module (IP150+)	4	✓	
Voice and Utility Reporting	-	VDMP3 ( Landline or GSM )	
Personal Dialing	-	*	
Pager Reporting	-	-	
Patented 2 opto coupler dialer circuit (US Patents 5751803, RE39406)	<b>~</b>	*	
In-field Firmware Upgrade	4	✓	
Auxiliary Output	4	4	
RF jamming supervision	4	4	
* - Any of which can be wireless			

<sup>\* =</sup> Any of which can be wireless

Pager support was removed starting with v6.80



Feature	SP4000	SP5500+	SP6000+	SP65	SP7000+
StayD	4	4	4	*	4
2 Serial Ports	-	4	*	-	4
Maximum Zones*	32	32	32	32	32
On-board Zones	4 (8 with ATZ)	-	8 (16 with ATZ)	9 (18 with ATZ)	-
Expansion Zones	24	24	24	24	16
Keypad Zones	15	15	15	15	15
Partitions	2	2	2	2	2
User Codes	32	32	32	32	32
PGMs	12	16*	16*	16*	16*
	(1 on-board)	(2 on-board)	(2+2** on-board)	(3 on-board)	(4 on-board)
PGM +/- Trigger	-	-	*	√(via BabyWare)	
Siren	Wired	Wired / Wireless with RTX3			
Alarm Relay	-	-	1**	-	1
Event Buffer	256	256	256	256	256
Wireless	4	4	4	4	4
Expansion					
2-Wire Smoke Detector Input	-	-	*	-	*
GPRS (PCS Series)	4	4	4	4	4
Compatible with IP150+	4	4	4	4	4
Compatible with	Landline or GSM	Landline only	Landline only	*	Landline only
VDMP3		3		(via PCS250)	
Patented 2 opto coupler dialer circuit	4	✓	1	-	1
In-field Firmware Upgradeable	4	✓	*	*	4

<sup>\*</sup> Any of which can be wireless
\* Optional

Pager support was removed starting with v6.80 GSM not supported on + panels