

# Proximity Mullion Readers 5002-0600



Stylish and fully featured Proximity readers from TDSi.

A stylish and full featured range of mullion readers from TDSi featuring proximity technologies.

TDSi is pleased to offer high quality mullion readers in robust polycarbonate housings with excellent read range.



## Features and Benefits.

### Fully encapsulated design

Provides maximum protection against water ingress making it suitable for mounting both indoor and out.

### Integral LEDs

Provides clear visual indication of access status.

### In-built sounder

Gives unambiguous feedback of card reads.

### Choice of output options

Allows connection to the majority of access control systems.

## Dimensions



Part No.	5002-0600
Dimension	45 x 130 x 17mm
Weight	250g
Operating Environment	-20°C to +55°C, 0 to 95% RH (non-condensing)
Power Supply	7 to 14VDC, 100mA (Max)
Operating Frequency	125KHz (nominal)
Card Technology	EM4100, EM4102, EM4200 or compatible
Sounder	Integral
LED's	RGB
Read Range*	<100mm (ISO card)
Output Formats	Magnetic Stripe, Wiegand 26-bit** / 34-bit / 37-bit

## Ordering Information

Part Number: 5002-0600

Description: Proximity Mullion Reader

\*Figures may vary between cards and installation

\*\*As standard. Contact TDSi for alternative configurations