



Analog

Dome

HCD-7030RA

QHD (4MP) Analog IR Dome Camera



Key Features

- 0.27 Lux@F2.0 (Color) (HCD-7020R/7030R), 0 Lux (B/W : IR LED on)
- Built-in 6.0mm fixed lens
- Day & Night (ICR), DWDR, Motion detection
- IR Viewable Length 30m
- Transmission distance max.500m
- Easy installation (Plug & play)

Compatible Accessories (Optional)



HCD-7030RA

QHD (4MP) Analog IR Dome Camera



Specifications

Video	
Imaging Device	1/3" 4MP CMOS
Resolution	2560x1440
Max. Framerate	30fps@4M(N), 25fps@4M(P)
Min. Illumination	Color: 0.27Lux(F2.0, 1/30sec) BW: 0Lux(IR LED on)
Video Out	BNC(AHD), additional CVBS for installation(2Pin connector type)
Video Transmission Distance	500m(5C2V Coaxial Cable)
Lens	
Focal Length (Zoom Ratio)	6.0mm fixed
Max. Aperture Ratio	F2.0
Angular Field of View	H: 49.02°, V: 27.61°, D: 55.60°
Min. Object Distance	0.5m(1.64ft)
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	0°~350° / 0°~67° / 0°~355°
Operational	
Day & Night	Auto(ICR)
Backlight Compensation	UserBLC, HLC, DWDR
Digital Noise Reduction	2DDNR
Motion Detection	4 zones
Privacy Masking	2 zones
Gain Control	Low / Middle / High / Very High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
Electronic Shutter Speed	1/30 ~ 1/12,000sec(N), 1/25~ 1/12,000sec(P)
Video Rotation	H-Rev/V-Rev
Analytics	Motion detection
IR Viewable Length	30m(98.43ft)
Coaxial Protocol	ACP(AHD Coax Protocol), CVBS: Pelco-C(Coaxitron)
Environmental & Electrical	
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH
Input Voltage	12VDC
Power Consumption	Max 5W
Mechanical	
Color / Material	Ivory / Plastic

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com

Hanwha Vision is formerly known as Hanwha Techwin.

Product Dimensions / Weight

Ø110.1 x 86.1mm(Ø4.33"x3.39"), 240g(0.53 lb)

HCD-7030RA

QHD (4MP) Analog IR Dome Camera



CAD

Unit:mm [inch]

