

Products

DVR

5100 SERIES

5200 SERIES

6100 SERIES

6200 SERIES

7100 SERIES

7200 SERIES

IP Camera

KIT

Network PTZ

NVR

Software

Transmission

Turbo HD Camera

Turbo HD PTZ

Wireless Series



HWD-5108MH(S)

HWD-5100MH SERIES TURBO HD DVR

- H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression
- HDTV/ AHD/ CVI/ CVBS/ IP video input
- Audio via coaxial cable
- Up to 5-ch IP camera input for HWD-5104MH (up to 1080p);
- Up to 10-ch IP camera input for HWD-5108MH (up to 5 MP)
- Max. 1200 m for 720p HDTV signal



Specification

Downloads

Product properties

Video/Audio input

Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Analog video input	8-ch
HDTV input	1080p25, 1080p30, 720p25, 720p30
AHD input	1080p25, 1080p30, 720p25, 720p30
HDCVI input	1080p25, 1080p30, 720p25, 720p30
CVBS input	Support
IP video input	2-ch (up to 10-ch) Up to 5 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Audio compression	G.711u
Audio input	1-ch RCA (2.0 Vp-p, 1 K Ω) 8-ch via coaxial cable
Video/Audio output	
HDMI/VGA output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz HDMI/VGA simultaneous output
Encoding resolution	When 1080p Lite mode not enabled: 720p/WD1/4CIF/VGA/CIF When 1080p Lite mode enabled: 1080p Lite/HD 720p Lite/WD1/4CIF/VGA/CIF
Main stream Frame rate	When 1080p Lite mode not enabled: For 720p stream access: 720p/WD1/4CIF/VGA/CIF@15 fps; For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) When 1080p Lite mode enabled: 1080p Lite/HD 720p Lite/WD1/4CIF/VGA/CIF@15 fps
Sub-stream Frame Rate	CIF/QVGA@25 fps (P)/30 fps (N)
Video bit rate	32 Kbps to 4 Mbps
Audio output	1-ch, RCA (Linear, 1 K Ω)
Audio bit rate	64 Kbps
Dual stream	Support
Stream type	Video, Video & Audio
Synchronous playback	8-ch

Network management

Remote connections	64
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS

Hard disk

SATA Interface	1 SATA interface
Hard Disk Capacity	Up to 4 TB capacity for each disk

External interface

Two-way audio input	Reuse the first audio input
Network interface	1, RJ45 10/100 Mbps self-adaptive Ethernet interface
USB interface	Rear panel: 2 × USB 2.0

General

Power supply	12 VDC, 1.5 A
Consumption (without HDD)	≤ 17 W
Working temperature	-10 °C to 55 °C (14 °F to +31 °F)
Working humidity	10% to 90%
Dimensions (W × D × H)	260 × 222 × 45 mm (10.2 × 8.7 × 1.8 inch)
Weight (without HDD)	≤ 1 kg (2.2 lb)

Information on this site does not constitute a public offer. Product description is for reference purposes. The manufacturer reserves the right to alter the appearance and characteristics of the product without prior notice.

Hikvision Europe
Dirk Storklaan 3, 2132 PX Hoofddorp, The Netherlands
Tel: +31-23-5542770
Fax: +31-23-5631112

[Privacy policy](#)
[Cookie policy](#)
General email: sales.eu@hikvision.com
Technical support: support.eu@hikvision.com

© COPYRIGHT, Hikvision Digital Technology Co.,
Ltd.. ALL RIGHTS RESERVED.