Product data sheet



ATS1500A-IP-MM-RK

Kit ATS1500A-IP-MM including ATS1115A keypad



Details

- 8 onboard zone inputs
- Max 32 zones: wired, wireless or mixed
- Economic input and output plug-in expansion
- Up to 16 shock sensor inputs
- 4 areas
- Up to 50 users
- EN50131 Grade 3 (when ATS-MM-TK added) / Environmental class 2
- USB port for local configuration
- Plug-on PSTN dialler for reporting or configuration
- Multilingual: language configurable per user
- Integrated 10/100Mb Ethernet connection
- IP alarm reporting to OH-NETREC receiver Optional GPRS
- Integrated access control & support for ATS125x door controller

ATS1500A-IP-MM-RK

Kit ATS1500A-IP-MM including ATS1115A keypad

Technical specifications

| System | |
|--------------------------|---------------------------|
| Product type | Integrated Access Control |
| Panel type | Hybrid |
| No. of keypads / readers | |
| Data Gathering Panels | 15 |
| (DGP) | |
| No. of alarm groups | 16 |
| Specified cable | WCAT52 |
| | WCAT54 |
| Inputs | |
| Max no. of inputs | 32 |
| Onboard inputs | 8 |
| Inputs plug-in expansion | າ 8 |
| 0.1.1. | |
| Outputs | |
| No. of outputs | 128 |
| No. of onboard outputs | 5 |
| Area | |
| No. of areas | 4 |
| User/Cards | |
| Max. no. of users | more than 1000 |
| Max. no. of cards | 2000 - 65532 |
| Max. no. of PIN codes | 2000 - 65532 |
| Access control | |
| Standard doors on | 4 |
| control panel | • |
| Door groups | 128 |
| Intelligent doors on | 28 |
| 4-door DGPs | |
| Communication | |
| Onboard transmission | IP . |
| type | |
| Transmission extension | GSM/GPRS, PSTN |
| Databus type | RS485 |
| Event log | |
| Alarm event log | 250-1000 |
| Access event log | 10000 |
| | |
| Electrical | |
| Power supply type | 230 VAC |
| Power supply value | 230 VAC +10%, -15%, 50 Hz |
| Mainboard current | 150 mA |
| consumption | |
| Max system current | 950 mA at 13.8 V ±0.2 V |
| Max aux power current | 840 mA |
| Auto-reset fuses | 5 |
| Glass break fuses | 1 |

| DL. | ! |
|-----|----------------|
| Pn | /sica |
| | / 3 104 |

| Physical dimensions | 315 × 388 × 85 mm | |
|------------------------|----------------------|--|
| Housing | Medium Metal | |
| Environmental | | |
| Operating temperature | -10 to +55°C | |
| Relative humidity | 95% (non-condensing) | |
| Environmental Class | Class II, indoor | |
| IP rating | 30 | |
| Standards & regulation | | |

| EN50131 Grade | Grade 3 |
|---------------|---------|
| Compliancy | CE |

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

