

# ATS624

## 4 Relay plug on card

### 4 relay plug-in output expander

The ATS624 offers a 4 relay output expansion to Advisor Advanced panels. To reduce required space in the Main control panel housing, the unit is a plug-in to the Main Control panel PCB.

The ATS624 provides for 4 outputs available through screw terminals, all supporting a 1A relay. In addition it provides an extension to connect 4 additional relays when using ATS1810, 4-way relay cards. The output function is defined through the output configuration in the main control panel.



### Details

- 4 outputs
- Relays
- 1A, NC/NO/C
- 4 additional Relay outputs through ATS1810
- Plug-in to Advisor Advanced panels
- Output switching current 1 A (

# ATS624

## 4 Relay plug on card

### Technical specifications

---

#### General

Expander type	Output expander
Product line	Advisor Advanced
Connection type	Plug-in
Max. per panel	1

#### Outputs

Total	8
Onboard	4
Expandable	4 (1x ATS1810)
Type of outputs	Relays
Relays	COM/NO/NC

#### Electrical

Operating voltage	10.5 to 13.8 VDC
Current consumption	50 mA

#### Physical

Physical dimensions	90 x 40 mm
---------------------	------------

#### Environmental

Operating temperature	0 to +50°C
Relative humidity	95% noncondensing max.
Environment	EN50130-5 ; Class II - Indoor (General)

#### Standards & regulation

Certification	EN50131 Grade 3, VdS
---------------	----------------------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 22 April 2020 - 17:19

