

Dimensions	268.1 x 136.5 x 31.1 mm (10.55 x 5.37 x 1.22")
Weight	700 g (1.54 lb)

---

## Hardware

Management Interface	(1) RJ45 Serial Port (10) Ethernet Ports (Default Port 0) (10) 10/100/1000 RJ45 Ports
Networking Interface	Port 0 Supports PoE IN Port 9 Supports PoE Out (2) 1 Gbps SFP Ports
Processor	4-Core 1 GHz MIPS64
System Memory	1 GB DDR3 RAM
On-Board Flash Storage	4 GB eMMC, 8 MB SPI NOR
Max. Power Consumption	20W (Excludes PoE Output)
Power Method	External AC/DC Power Adapter, 24W (24V, 1A) (Included) 24V Passive PoE
Power Supply	External AC/DC Adapter
Passive PoE Voltage Range Max. Wattage per Port	DC/PoE Passthrough 20W (24V)
Supported Voltage Range	9 - 30VDC
Button	Reset
LEDs System Data Ports SFP Data Port	Power Speed/Link/Activity;PoE (Ports 0 and 9 only) Link/Activity
ESD/EMP Protection	Air: $\pm 24$ kV, Contact: $\pm 24$ kV
Operating Temperature	-10 to 50° C (14 to 122° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC