




Product descriptionSingle cylinder to be used with mortice lock cases and other applications with DIN / Europrofile

Lock is operated by key from outside.

- Overview of Advantages
 Can be use with wide range applications for DIN cylinders
 Suitable for both outer and inner door use
- Adjustable length with extension system to match different door thicknesses Adjustable locked position of cam
- Several plating options





Technical data

Available key systems	ABLOY PROTEC, ABLOY PROTEC ² , ABLOY NOVEL, ABLOY CLASSIC, ABLOY SENTO
Available plating options	Bright chrome (Cr), Satin chrome (HCr), Brushed nickel (NiHa), Bright brass (MSKiLa), Satin brass (MSHaLa)
Cylinder cross section according standard DIN 18252	
Cylinder length	PROTEC ² 31mm, NOVEL 33mm
Length adjustable	with 5mm steps 31–81mm, with 10mm steps 81–131mm
Weight	0,17kg

This content is protected by Intellectual Property Rights Laws. The title to the content shall not pass to you, and instead shall remain with Abloy Oy or a third party holding the title. Abloy develops continuously the products and solutions offered. Therefore, the information contained in the document is subject to change without notice. ABLOY PROVIDES THIS CONTENT ON AN "AS IS" BASIS WITHOUT ANY WARRANTIES OF ANY KIND, EXPRESS, IMPLIED, OR STATUTORY."

