

ACSⁱ -101

PROFESSIONAL WIRELESS ONE-CHANNEL ALARM SYSTEM SET INSTRUCTION MANUAL AND TECHNICAL SPECIFICATIONS

INTRODUCTION.

ACS-101 is the wireless one-channel multi purpose alarm system set designed for use as a Panic Button in security systems and for remote control of ELECTRICAL GATES, SLIDING DOORS, ELECTROMAGNETIC LOCKS, AUTOMATIC BARRIERS, ELECTRICAL CURTAINS, LIGHTING FIXTURES, etc.

ACS-101 FEATURES.

• FOUR OPERATING MODES OF THE RECEIVER:

1. PANIC BUTTON MODE (SECURITY)
2. SWITCHING MODE (ON/OFF).
3. HOLD MODE (CONTINUOUS)
4. PULSE MODE - 1SECOND

- Receiving range in open space - up to 250 meters
- Maximum quantity of remote controls learning the receiver . 680 pieces
- Easy learning of the receiver by additional remote controls
- Unauthorized access protection (in %Panic Button+mode)
- Last event memory: 30min (in %Panic Button+mode)
- The alarm comes on when the electric power supply is disconnected (in %Panic Button+mode).

SETTING THE RECEIVER OPERATING MODES.

1. «PANIC BUTTON MODE».

SETTING THE RECEIVER OPERATING MODE

Jumper %SEC-1+ is installed. Jumper %LG-1+ is installed.

This mode is used in security systems. The alarm occurs by pressing the remote control button, by unauthorized receiver opening, or when the electric power supply is disconnected.
Last event memory - 30 minutes.

ATTENTION! In the «PANIC BUTTON MODE» the receiver does not operate if the cover is removed.

2. «SWITCHING MODE» (ON/OFF).

SETTING THE RECEIVER OPERATING MODE

Jumper %SEC-1+ is installed. Jumper %LG-1+ is removed.

Each pressing the remote control button corresponds to one of the relay positions (ON/OFF).

3. «HOLD MODE (CONTINUOUS)».

SETTING THE RECEIVER OPERATING MODE

Jumper %SEC-1+ is removed. Jumper %LG-1+ is installed.

The receiver relay is activated during the continuous pressing the remote control button.

4. «PULSE» MODE» - 1 SECOND.

SETTING THE RECEIVER OPERATING MODE

Jumper %SEC-1+ is removed. Jumper %LG-1+ is removed.


Pressing the remote control button activates the relay for 1 second.

RECEIVER CONNECTION.

Run the cable through the cable entry hole and connect the wires in accordance to the following instructions:
Terminals 1, 2 (marked -12V+) - for power supply.
Terminals 3, 4, 5 . relay output.


CONNECTING THE RECEIVER IN

«PANIC BUTTON MODE»



CONNECTING THE RECEIVER IN THE FOLLOWING MODES:

«SWITCHING MODE» (ON/OFF)
«HOLD MODE» (CONTINUOUS)
«PULSE MODE»



MEMORY CLEARING.

1. Disconnect power.
2. Remove jumper %RN+.
3. Restore power . LED starts blinking for 5 seconds and then will be OFF. All pre-programmed codes are erased.
4. Replace jumper %RN+.
5. Start new learning of the receiver.

LEARNING OF THE RECEIVER.

1. Remove jumper %RN+. LED will be OFF.
 2. Press any of the remote control buttons . the receiver's LED will flash once indicating successful code memorizing . the receiver is learned by the remote control.
If necessary, learn the receiver by additional remote controls.
 3. Replace jumper %RN+.
 4. Repeat steps 1-3 to learn the receiver by additional remote controls.
- Maximum quantity of remote controls learning the receiver . 680 pieces.

RECEIVING RANGE.

The operating range of the hand-held remote controls depends on the mounting location of the receiver. The various obstructions, the environmental factors, the radio-frequency and electromagnetic sources might influence the emission of radio-signal and as a result, might shorten the receiving range. For optimal radio-signal reception: mount the receiver at least 1.5 meter above the ground, as far as possible from any radio frequency and electromagnetic sources.

TECHNICAL SPECIFICATIONS.

Power input: 12-16VDC;	Alarm period (in panic button mode): 3sec;
Current consumption:	Last event memory (in panic button mode): 30min;
In stand-by mode: 15mA/12V;	Dry contact relay: DC30V/1.0A; DC60V/0.3A; AC125V/0.5A;
In active mode: 28mA/12V;	Opening protection: tamper switch;
Receiving range in open space: up to 250m;	Operating temperature range: -20°C +50°C;
Operating frequency: 433.92MHz ±50kHz;	Storage temperature range: -40°C +80°C;
Radiated power: 5mW;	Dimensions: 85mm x 40mm x 20mm;
Memory capacity: 330codes;	Weight: 125gr.
Warm up period: 0.5sec;	

WARRANTY. GSN ELECTRONIC COMPANY LTD., warrants the product to be free from defects in materials and workmanship under condition of observance of service regulations and to be repaired or replaced under absence of mechanical damages for a limited period of five years from the date of sale.



GSNTM Electronic Company Ltd.

7 ATARA ST., NAZARETH ILLIT 17802, P.O.BOX 17719, ISRAEL
TEL: 972 4 6467152, FAX: 972 4 6562414

WWW.GSNCOMPANY.COM