# MARINE

## Your Safety, Our Technology



#### **Features**

- ▶ Low Profile, only 8mm
- Rugged design
- Dedicated cable screen terminal
- Accepts from 1 to 2.5 mm<sup>2</sup> cables
- Quick connection via square cable clamps
- Electronics free



#### Description

Model YBN-R/4(IS) is a Conventional Detector Mounting Base which should be used in conjunction with the SIL2 approved range of Intrinsically Safe detectors It is supplied with square cable clamps for secure and reliable cable termination but the base does not provide line continuity during detector removal, therefore if Call Points are being used then these should be wired onto the zone first.

#### Specification (add details below)

Maximum Humidity	95%RH - Non Condensing (at 40 °C)
Colour / Material	Ivory or White / ABS
Weight (g) / Diameter (mm) / Height (mm)	51 / 100 / 8
Fixing Centres (mm)	48 ~ 74
Maximum Wire Thickness	2.5 mm <sup>2</sup> Cables

### **Ordering Codes**

#### Product

Conventional Detector Mounting Base Conventional Detector Mounting Base (White)

#### **Part Number**

YBN-R/4(IS) YBN-R/4(IS) WHT



For further information visit www.hochikieurope.com/marine

Hochiki Europe (UK) Ltd. Reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. To be a complete and up-to-date description.