




I-CON wallbox is the JOINON solution for private and semi-public contexts, in compliance with the international standard IEC 61851-1 ed. 3. They are characterized by an elegant and compact design, for the special "one-hand recharge" functionality, and for the presence of the vandal-proof socket as an alternative to the connector with cable and holder integrated in the station, the IP55 degree combined with an IK10 certified resistance, intelligent load management, Backlight lighting, and various installation possibilities: wall, flush-mounting or floor.

| INPUT | | - Socket/Connector Nr. (Type) | | 1 (Type 2 socket, with shutters) |
|--------------------------------------|------------------------|-------------------------------|--|---|
| Terminal blocks | 5 x 10 mm ² | Charging activation | | Free access |
| Current nominal | 32 A | Human Interface | | Led RGB |
| Total power | 22 Kilowatt | Connectivity | | Nu |
| OUTPUT | | - MECHANICAL FACTS | | |
| Tensiune nominală | 400 V | Mouting and installation | | Wall mounting (floor mounting with support) |
| Current supplied (max) | 32 A | Culoare | | Gri închis |
| Maximum current | 22 Kilowatt | Material | | Thermoplastic (Post-industrial origin) |
| Thermal-magnetic protection | Currently not present | External treatments | | Nu |
| Tip de protecție diferențială | Currently not present | Clasă de protecție IP | | IP55 |
| Contor energie | Currently not present | Cod IK | | IK10 |
| DC Leakage check | Da | Temperatură de operare | | -25 +50 °C |
| (Auto)restart electrical protections | Currently not present | Customizations | | Yes (front) |

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK

IK10

STANDARDS/APPROVALS

