




I-CON wallbox is the JOINON solution for private and semi-public contexts, in compliance with the international standard IEC 61851-1 ed. 3. They are characterized by an elegant and compact design, for the special "one-hand recharge" functionality, and for the presence of the vandal-proof socket as an alternative to the connector with cable and holder integrated in the station, the IP55 degree combined with an IK10 certified resistance, intelligent load management, Backlight lighting, and various installation possibilities: wall, flush-mounting or floor.

INPUT		- Socket/Connector Nr. (Type)	1 (Type 2 connector with 5 mt. cable)
Terminal blocks	3 x 10 mm ²	Charging activation	Locally managed, via RFID
Current nominal	32 A	Human Interface	Led RGB
Total power	7.4 Kilowatt	Connectivity	Nu
OUTPUT		- MECHANICAL FACTS	-
Tensiune nominală	230 V	Mouting and installation	Wall mounting (floor mounting with support)
Current supplied (max)	32 A	Culoare	Gri închis
Maximum current	7.4 Kilowatt	Material	Thermoplastic (Post-industrial origin)
Thermal-magnetic protection	Currently not present	External treatments	Nu
Tip de protecție diferențială	Currently not present	Clasă de protecție IP	IP55
Contor energie	Currently not present	Cod IK	IK10
DC Leakage check	Da	Temperatură de operare	-25 +50 °C
(Auto)restart electrical protections	Currently not present	Customizations	Yes (front)

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK

IK10

STANDARDS/APPROVALS

