



# TO.GO A




## ADVANCED ROLLING CODE TRANSMITTERS

2 and 4 channels



### Configuration and list of available channels:

	CH1		CH5
	CH2		CH6
	CH3		CH7
	CH4		CH8
	hidden button		CH9



### Training

Guide to memorisation of a TO.GO transmitter in a receiver or control unit. Watch the video.

- 2 or 4-channel transmitter of the TO.GO series with Advanced Rolling Code
- The new ARC coding guarantees maximum security due to the length of the transmitted code (128 bit) and the high number of possible combinations
- The TO.GO4A model allows users to set up to 9 channels, thanks to the option of activating the command by simultaneously pressing two buttons chosen by the user. This function allows avoiding accidental openings caused by pressing a button by mistake and is particularly indicated for use with alarm systems
- Equipped with 12 V battery for long lifespan
- Long range, up to 230 m in a free area
- Car accessory (TO.CLIP) or wall accessory (SMART) available



#### ONE.2WO

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



#### ONE.2WB

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, in box. 512 memorisable codes.



#### ONE.2WI

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, plug-in. 512 memorisable codes.



#### ONE.4WB

4-channel receiver with full-range power supply (115-230 VAC/DC) and triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



#### CALL

Four-channel GSM receiver, up to 4 automations control without limits of distance. Makes it possible to use the device by means of a mobile telephone.



#### MEM2048

Additional memory for up to 2048 codes. For receivers of the ONE series.



**TO.GO2A**

2-channel transmitter with Advanced Rolling Code.



**TO.GO4A**

4-channel transmitter with Advanced Rolling Code.



**TO.GO2AS**

2-channel transmitter with Advanced Rolling Code. Sequential coding for multiple insertions.




**TO.GO4AS**

4-channel transmitter with Advanced Rolling Code. Sequential coding for multiple insertions.




**AWO**

433.92 MHz antenna for external installation with IP54 box, fitted with shielded RG58 5 m cable.




**RG58 MT5**

AWO antenna cable L = 5 m.




**AW**

433.92 MHz stylus antenna for external installation, equipped with a shielded 3m RG58 cable.




**SMART**

Cover compatible with TO.GO transmitters for internal wall mounting.



**TO.CLIP**

Car accessory for TO.GO transmitters.



**BT12**

12 V Battery, for transmitter. Available in 50 pcs packing.



# TO.GO VA



## TRANSMITTERS WITH DOUBLE CODING, ADVANCED ROLLING CODE AND ROLLING CODE


2 and 4 channels



### Configuration and list of available channels (ARC only):

	CH1		CH5
	CH2		CH6
	CH3		CH7
	CH4		CH8
	hidden button		CH9

- 2 or 4-channel transmitter with double coding, Advanced Rolling Code and Rolling Code.
- The new ARC coding guarantees maximum security due to the length of the transmitted code (128 bit) and the high number of possible combinations
- The transmitter has ARC coding as factory setting. However, it is possible to change the coding by using it in Rolling Code or even in mixed coding (ARC and Rolling Code)
- If using mixed coding, the ARC can be set with the T1/T3 buttons and the Rolling Code with the T2/T4 buttons
- The TO.GO4VA model allows users to set up to 9 channels, thanks to the option of activating the command by simultaneously pressing two buttons chosen by the user. This function allows avoiding accidental openings caused by pressing a button by mistake and is particularly indicated for use with alarm systems
- Equipped with 12 V battery for long lifespan  
Long range, up to 230 m in a free area
- Car accessory (TO.CLIP) or wall accessory (SMART) available




### Training

Guide to memorisation of a TO.GO transmitter in a receiver or control unit and how to change the code. Watch the video.



#### ONE.2WO

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



#### ONE.2WB

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, in box. 512 memorisable codes.



#### ONE.2WI

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, plug-in. 512 memorisable codes.



#### ONE.4WB

4-channel receiver with full-range power supply (115-230 VAC/DC) and triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



#### CALL

Four-channel GSM receiver, up to 4 automations control without limits of distance. Makes it possible to use the device by means of a mobile telephone.



#### ONE.2QB

Universal 868 MHz receiver, 2 channels, in box.  
**ONE.2QI**  
Universal 868 MHz receiver, 2 channels, plug-in.



**TO.GO2VA**

2-channel transmitter with Advanced Rolling Code and Rolling Code.



**TO.GO4VA**

4-channel transmitter with Advanced Rolling Code and Rolling Code.



**TO.GO4QV**

4-channel 868 MHz transmitter with Rolling Code.



**MEM2048**

Additional memory for up to 2048 codes. For receivers of the ONE series.




433,92 MHz

**AWO**

433.92 MHz antenna for external installation with IP54 box, fitted with shielded RG58 5 m cable.

**RG58 MT5**

AWO antenna cable L = 5 m.



433,92 MHz


**AW**

433.92 MHz stylus antenna for external installation, equipped with a shielded 3m RG58 cable.




**SMART**

Cover compatible with TO.GO transmitters for internal wall mounting.



**TO.CLIP**

Car accessory for TO.GO transmitters.



**BT12**

12 V Battery, for transmitter. Available in 50 pcs packing.




# TO.GO AK

## TRANSMITTERS WITH DOUBLE CODING, ADVANCED ROLLING CODE AND FIXED CODE

Compatible with the most common fixed code transmitters

2 and 4 channels



### Training

Guide to the procedure of copying fixed codes and enabling ARC codes. Watch the video.

- 2 or 4-channel transmitter with double coding, Advanced Rolling Code and Fixed Code
- The new ARC coding guarantees maximum security due to the length of the transmitted code (128 bit) and the high number of possible combinations
- The transmitter allows expanding the convenience of remote duplication (without having access to the installation), typical of Fixed Codes, even with ARC. TO.GO2/4AK transmitters can become duplicates of fixed code transmitters, but they can also be enabled to operate systems with Advanced Rolling Code
- It is possible to associate each button with different types of coding (Advanced Rolling Code or Fixed Code) independently
- Equipped with 12 V battery for long lifespan
- Long range, up to 230 m in a free area
- Car accessory (TO.CLIP) or wall accessory (SMART) available



#### ONE.2WO

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



#### ONE.2WB

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, in box. 512 memorisable codes.



#### ONE.2WI

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, plug-in. 512 memorisable codes.



#### ONE.4WB

4-channel receiver with full-range power supply (115-230 VAC/DC) and triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



#### CALL

Four-channel GSM receiver, up to 4 automations control without limits of distance. Makes it possible to use the device by means of a mobile telephone.



#### MEM2048

Additional memory for up to 2048 codes. For receivers of the ONE series.



**TO.GO2AK**

2-channel transmitter with Advanced Rolling Code and Fixed Code.



**TO.GO4AK**

4-channel transmitter with Advanced Rolling Code and Fixed Code.



**AWO**

433.92 MHz antenna for external installation with IP54 box, fitted with shielded RG58 5 m cable.



**RG58 MT5**

AWO antenna cable L = 5 m.




**AW**

433.92 MHz stylus antenna for external installation, equipped with a shielded 3m RG58 cable.




**SMART**

Cover compatible with TO.GO transmitters for internal wall mounting.



**TO.CLIP**

Car accessory for TO.GO transmitters.



**BT12**

12 V Battery, for transmitter. Available in 50 pcs packing.