



Company Overview

CAV-72B

*Power source: AC 100V-240V, 50/60Hz(Free voltage) / 17W

* Display: 7 inch wide TFT LCD

- Mounting type : Wall surface mounted type

• Wiring: 1)CDS-4CM(Video distributor unit): 6wires 2)Monitor unit: 6 wires

- Distance : CAV-72B to CAV-71B : 20m(Ф0.65)

- Communication : Handset & Hands free

. On-screen duration : 60 ±30 sec Temperature : 0°C ~ +40°C (32°F ~ 104°F)

- Image record : 128 cuts

- Dimension: 314 x 173 x 44(mm)

CDT-180

- Power source : Ni-MH 1.2V 600mA, AAAx3(Handset)

- Distance : Outdoor Max 200m / Indoor Max 40m

* Dimensions: 1) Handset: 28 x 46.5 x 115(mm) 2) Base station: 133 x 81.5 x 52.5(mm)

Functions

CAV-72B

*Up to 4 DECT phones per CAV-72B.

*Up to 4 cameras and up to 20 monitors are connected through CDS-4CM.

• 7 inch TFT LCD is applied to see a visitor for high resolution quality.

. Reviewing the image of a visitor when being away

Intercom function
Monitoring & talk with a visitor

- Door lock release - OSD interface - Telephone receiving.

CDT-180

*Talk with a visitor * Telephone function * Door lock release

- Max 100 of telephone directory - Intercom function between DECT phone

- Max 10 of redial number directory









บริษัท ควินตัส อุตสาหกรรม จำกัด QUINTUS INDUSTRY Co.,Ltd.









