

MONITOR

CDV-70M



PRODUCT FUNCTION

- 7 inch TFT LCD screen
- Video talk and door lock release enable (both individual and public entrance)
- Support 2 Monitors, 2 Cameras and 2 Interphones
- PAL/NTSC convertible

SPECIFICATION

Power source	AC 100-240V, 50/60Hz
Display	7inch wide color LCD
Mount type	Wall-mounted type
Operating temp.	0°C~40°C
Wiring	Door camera : 4wires / Interphone : 4wires
Distance	Door camera : 28m (0.5Ø) / Interphone : 30m(0.65Ø)
Consumption	Max.10W/standby 3.4W
Dimension(mm)	244(W)×180(H)×18(D)

MONITOR

CDV-43M



PRODUCT FUNCTION

- 4.3 inch TFT LCD screen
- Video talk and door lock release enable (both individual and public entrance)
- Support 2 Monitors, 2 Cameras and 2 Interphones
- PAL/NTSC convertible

SPECIFICATION

Power source	AC 100-240V, 50/60Hz
Display	4.3 inch LED Display
Mount type	Wall-mounted type
Operating temp.	0°C~40°C
Wiring	Door camera : 4wires / Interphone : 4wires
Consumption	Maximum : 15W
Distance	Door camera : 28m (0.5Ø) / Interphone : 30m (0.65Ø)
Dimension(mm)	180(W)×180(H)×28(D)

MONITOR

CDV-72UM (MOTION DETECTION)



PRODUCT FUNCTION

- Video talk and door lock release enable
- Store video & still image through real-time monitoring & motion detection
- Long range communication with CCTV (Optional support MEGA-Q)
- Memory storing in SD card
- Expandable up to 2 monitors with 2 CCTV cameras and 2 door cameras
- Full touch screen • PAL/NTSC convertible
- DRC-40KA connectable

SPECIFICATION

Power source	AC 100-240V, 50/60Hz
Display	7 inch wide color LCD
Mount type	Wall-mounted type
Operating temp.	0°C~40°C
Wiring	Door camera: 4 wires Interphone: 4 wires CCTV camera : 2wires
Distance	Door camera : 50m (0.65Ø) Interphone : 30m (0.65Ø)
Consumption	Max.16W/standby 4.6W
Dimension(mm)	276(W)×178(H)×31(D)