

Code: VTO4202F-P-S2

VIDEO DOORPHONE **VTO4202F-P-S2** DAHUA

The module is designed for installation in DAHUA VTM12x series housings.

Attention! When selecting 2-wire devices, check the compatibility list available at the bottom of the page in the "files" section.

It is a hybrid module - it can work in a 2-Wire installation or as a standard IP video doorphone.



Sensor:	2 Mpx CMOS
Lens:	1.9 mm
View angle:	160 °
proximity reader built-in:	—
Image compression method:	H.265
LED illuminator:	—
IR illuminator:	✓
Compatibility:	DAHUA
RS-485:	✓
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS



Main features:	<ul style="list-style-type: none"> • Bidirectional communication, • Microphone built-in, • Speakers built-in • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Power output : 12 V DC / 100 mA, • Tamper detection - removing from mounting surface ,
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 2-Wire IP interface
Power consumption:	≤ 12 W
Housing:	Aluminum
Color:	Silver
"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
IK rating:	IK07
Operation temp:	-30 °C ... 60 °C
Weight:	0.28 kg
Dimensions:	100 x 100 x 49.3 mm
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years