



Datasheet UVC-G4-Doorbell-EU





## UniFi Protect G4 Doorbell

UVC-G4-Doorbell-EU\* is a Wi-Fi video doorbell with a built-in display and real-time two-way audio communication. The camera features a high-quality 5MP sensor with enhanced night vision. Image streams can be viewed in up to 1600 x 1200 (2 MP) HD at 30 FPS. UVC-G4-Doorbell-EU includes a PIR sensor for instant motion detection alerts. Integration with UniFi Protect provides an easy-to-use interface.





## Mechanical

Dimensions	118.3 x 46.8 x 25.8 mm (4.66 x 1.84 x 1.02")
Weight	Without Mount: 130 g (4.59 oz) With Flat Wall Mount: 178 g (6.28 oz)
	With 20° Wedge Mount: 200 g (7.05 oz)
Enclosure Material	Polycarbonate
Mount Materials	Flat Wall Mount: Aluminum Alloy
	20° Wedge Mount: Polycarbonate
Weatherproofing	IPX4
Optics	
Sensor	5 MP CMOS Sensor

Sensor	5 MP CMUS Sensor
Lens	Fixed Focal Length
View Angle	H: 138°, V: 114°, D: 155°
Night Mode	Built-in IR LED Illumination and IR Cut Filter

## Video

Video Compression	H.264
Resolution	1600 x 1200 (4:3)
Maximum Frame Rate	30 FPS

## System

Processor Specs	Ambarella Advanced Image Processing SoC
Memory Information	512 MB
Mangement Interface	UniFi Protect
Networking Interface	802.11 ac Wi-Fi
Flash Memory Support	256 MB
Max. Power Consumption	12VA
Power Requirements	16-24VAC, 20VA, 50/60 Hz
Link/Activity LED	Yes
Button	Factory Reset
Mounting	Flat Wall/20° Wedge (Kits Included)
Operating Temperature	-10 to 40° C (14 to 104° F)

Operating Humidity	0 to 90% Noncondensing
Certifications	FCC, IC, CE
Audio	
Microphone	Yes (Can be Disabled in Software)
Speaker	Yes
Software	
Controller Software	UniFi Protect
Mobile Apps	UniFi Protect iOS and Android
Transformer Specifications	
Input Rating (5, 6)	230V, 50/60Hz
Output Rating (1, 4)	16VAC, 15VA
Operating Temperature	-5 to 35 ° C (23 to 95° F)

Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at: www.ui.com/support/warranty